

Material designation				Hollow Rods									
				ØDrawn		ØExtruded	Sections-Drawn		Sections-Extruded	Round and polygonal			
Standards				Outside-Ø mm			Width across flat mm			Inside-Ø mm		Wall thickness mm	
Code	Sembol	EN NO	UNS NO	min.	max.	max.	min.	max.	max.	min.	max.	min.	max.
<a href="#">KALİBRE</a>	CuZn39Pb3	CW614N	C38500	23,5	80	80	22	74	77	13	59	3	25
<a href="#">PRES</a>	CuZn40Pb2	CW617N	C38000	23,5	80	80	22	74	77	13	59	3	25
<a href="#">DZR</a>	CuZn36Pb2As	CW602N	C35330	23,5	80	80	22	74	77	13	59	4	25
<a href="#">S608</a>	CuZn38Pb2	CW608N	C35000	23,5	80	80	22	74	77	13	59	4	25
<a href="#">S612</a>	CuZn39Pb2	CW612N	C37700	23,5	80	80	22	74	77	13	59	4	25
<a href="#">S603</a>	CuZn36Pb3	CW603N	C36000	23,5	80	80	22	74	77	13	59	4	25
<a href="#">Ecobras®</a>	~CuZn21Si3P	CW724R	C69300	23,5	80	80	22	74	77	13	59	4	25
<a href="#">S509</a>	CuZn40	CW509L	C27450	23,5	80	80	22	74	77	13	59	3	25
<a href="#">S510</a>	CuZn42	CW510L		23,5	80	80	22	74	77	13	59	3	25
<a href="#">S511</a>	CuZn38As	CW511L		23,5	80	80	22	74	77	13	59	4	25
<a href="#">SİYAH-YEŞİL</a>	DIN CuZn38Pb1,5		-	23,5	80	80	22	74	77	13	59	4	25
<a href="#">S601</a>	CuZn35Pb2	CW601N	C34200	23,5	80	80	22	74	77	13	59	4	25
<a href="#">S606</a>	CuZn37Pb2	CW606N	C35300	23,5	80	80	22	74	77	13	59	4	25
<a href="#">S607</a>	CuZn38Pb1	CW607N	-	23,5	80	80	22	74	77	13	59	4	25
<a href="#">S622</a>	CuZn43Pb1Al	CW622N	-	23,5	80	80	22	74	77	13	59	3	25
<a href="#">S624</a>	CuZn43Pb2Al	CW624N	-	23,5	80	80	22	74	77	13	59	3	25
<a href="#">S626</a>	CuZn33Pb1,5AlAs	CW626N	-	23,5	80	80	22	74	77	13	59	4	25
<a href="#">Mavi-Hi</a>	DIN CuZn40Mn1Pb		-	23,5	80	80	22	74	77	13	59	3	25

